



A Two-Dimensional Transverse Magnetic Propagation Model of a Sine Wave Using Mur Boundary Conditions

by T. A. Korjack

ARL-TR-1379

June 1997

19970703 079

Approved for public release; distribution is unlimited.

The findings in this report are not to be construed as an official Department of the Army position unless so designated by other authorized documents.

Citation of manufacturer's or trade names does not constitute an official endorsement or approval of the use thereof.

Destroy this report when it is no longer need. Do not return it to the originator.

Army Research Laboratory

Aberdeen Proving Ground, MD 21005-5067

ARL-TR-1379

June 1997

A Two-Dimensional Transverse Magnetic Propagation Model of a Sine Wave Using Mur Boundary Conditions

T. A. Korjack

Information Science and Technology Directorate, ARL

Abstract

A two-dimensional (2-D) transverse magnetic formulation of a propagating sine wave source disturbance was numerically simulated using the finite difference-time domain (FD-TD) methodology. The nonreflecting boundary conditions due to Mur were used at the boundary surfaces. Electric field intensity distributions resulted over a progressive time expansion to illustrate the propagation effect over the entire 2-D mesh. The imposition of the Mur boundary algorithm produced accurate results when the second approximation was used and when the source was located reasonably far from the mesh boundary.

TABLE OF CONTENTS

		<u>Page</u>
	LIST OF FIGURES	v
1.	INTRODUCTION	1
2.	MATHEMATICAL AND NUMERICAL REVIEW	2
2.1	Difference Equations and Node Distribution	2
2.2	Stability Condition	3
2.3	Mur Absorbing Boundary Conditions	4
2.4	Sine Wave Pulse	5
3.	SUMMARY/RESULTS	6
4.	REFERENCES	13
	DISTRIBUTION LIST	15
	REPORT DOCUMENTATION PAGE	17

INTENTIONALLY LEFT BLANK.

LIST OF FIGURES

<u>Figure</u>	<u>Page</u>
1. Distribution of electric field intensity (V/m) at time step = 50	7
2. Distribution of electric field intensity (V/m) at time step = 75	8
3. Distribution of electric field intensity (V/m) at time step = 100	9
4. Distribution of electric field intensity (V/m) at time step = 150	10
5. Distribution of electric field intensity (V/m) at time step = 200	11

INTENTIONALLY LEFT BLANK.

1. INTRODUCTION

The two-dimensional (2-D) finite difference formulation of time domain electromagnetic-field problems is a convenient tool for solving scattering problems. It can be easily applied to conducting obstacles as well as magnetic obstacles that can be homogeneous or inhomogeneous of arbitrary shape. When a space-time mesh is implemented and Maxwell's equations are replaced by a system of finite-difference equations on the mesh for a problem dealing with an open domain, there exists the imposition of boundary conditions for an open system (i.e., the domain in which the field has to be computed is unbounded). A methodology for limiting the domain in which the field is computed is effectuated by using a mesh of limited size, but yet large enough to contain the obstacle, and by using a boundary condition on the outer surface of the mesh, such that the unbounded surrounding is modeled as accurately as practicable. Boundary conditions of this type are called absorbing boundary conditions. Many authors have proposed methods for absorbing boundary conditions, such as Taylor (1969), Taflove and Brodwin (1975), Taflove (1980), Merewether (1971), and Kunz and Lee (1978).

However, all of these previous methods have the disadvantage of causing considerable reflections when the fields near the boundary of the mesh do not propagate in a specific direction. In this report, a potentially superior method will be implemented based upon Engquist and Majda (1977) and especially upon Mur (1981), to simulate a 2-D transient transverse magnetic (TM) distribution of electric and magnetic field intensities for a typical sine wave propagating from the center outward in all directions using the Mur absorbing boundary conditions. This analysis will demonstrate, in a limited way, how electromagnetic waves can propagate, emanating from a source of electromagnetic disturbance as typified in one of the gas turbine engine components. It is hoped that this study will serve as a starting point to look at the electromagnetic interference (EMI) produced by a starter, causing the analog electronic control unit diagnostic connector to abort the actual start of the gas turbine engine.

Frequency domain characteristics for the scattered signal can be obtained by Fourier transformation of the time-domain scattered signal. The previously mentioned problem is solved by

a FORTRAN program that can numerically compute, using the finite difference-time domain (FD-TD) method, the scattered fields of a sine wave source emanating from the center of the mesh.

Hence, the mathematical and numerical background of the FD-TD approach is reviewed for the simplifying case of TM excitation in a 2-D space. Discretization of Maxwell's equations for lossy media, stability, simulation of absorbing boundary conditions, and scattered field formulation are also discussed.

2. MATHEMATICAL AND NUMERICAL REVIEW

The FD-TD method, proposed by Yee (1966), is the direct solution of the time-dependent Maxwell curl equations. For this method, difference approximations are applied to both space and time derivatives in Maxwell's equations. By knowing the initial, boundary, and source conditions, equations are solved using the time-marching procedure. The actual wave propagations and interactions are thus simulated in numerical computations.

2.1 Difference Equations and Node Distribution. Maxwell's equations governing the propagation of electromagnetic waves in an isotropic, homogeneous medium are:

$$\frac{\partial \vec{H}}{\partial t} = -\frac{1}{\mu} \nabla \times \vec{E} \quad (1)$$

$$\frac{\partial \vec{E}}{\partial t} = \frac{1}{\epsilon} [\nabla \times \vec{H} - \sigma \vec{E}], \quad (2)$$

where μ , ϵ , and σ can be functions of space.

For a TM spatial lattice in a 2-D rectangular (x,y) coordinate system, equations 1 and 2 can be discretized as:

$$H_x^{n+\frac{1}{2}} \left(i, j + \frac{1}{2} \right) = H_x^{n-\frac{1}{2}} \left(i, j + \frac{1}{2} \right) - \frac{\Delta t}{\mu} \left[\frac{E_z^n(i, j+1) - E_z^n(i, j)}{\Delta h} \right] \quad (3)$$

$$H_y^{n+\frac{1}{2}} \left(i + \frac{1}{2}, j \right) = H_y^{n-\frac{1}{2}} \left(i + \frac{1}{2}, j \right) + \frac{\Delta t}{\mu} \left[\frac{E_z^n(i+1, j) - E_z^n(i, j)}{\Delta h} \right] \quad (4)$$

$$E_z^{n+1}(i, j) = \left[\frac{1 - \frac{\Delta t \sigma}{2\epsilon}}{1 + \frac{\Delta t \sigma}{2\epsilon}} \right] E_z^n(i, j) + \left[\frac{\frac{\Delta t}{\epsilon \Delta h}}{1 + \frac{\Delta t \sigma}{2\epsilon}} \right]$$

$$\left[H_y^{n+\frac{1}{2}} \left(i + \frac{1}{2}, j \right) - H_y^{n+\frac{1}{2}} \left(i - \frac{1}{2}, j \right) - H_x^{n+\frac{1}{2}} \left(i, j + \frac{1}{2} \right) + H_x^{n+\frac{1}{2}} \left(i, j - \frac{1}{2} \right) \right], \quad (5)$$

where Δt and Δh are time and space steps, respectively.

For inhomogeneous media with continuous variation of material constants ϵ , μ , and σ , no additional work needs to be done except specifying ϵ , μ , and σ at each grid point. However, for heterogeneous media where step changes of material constants occur at interfaces of adjacent homogeneous media, some spatial treatments are necessary. Since it is assumed that no conductive media are immersed in the propagation field in this analysis, then the σ terms will not appear in the program.

2.2 Stability Condition. If the FD-TD method is to have a stable solution, the Courant stability condition must be satisfied:

$$V_m \Delta t \leq \frac{1}{\sqrt{\left(\frac{1}{\Delta x}\right)^2 + \left(\frac{1}{\Delta y}\right)^2 + \left(\frac{1}{\Delta z}\right)^2}}, \quad (6)$$

where V_m is the velocity of light in the medium. When $\Delta x = \Delta y = \Delta z = \Delta h$, equation 6 is simplified to

$$V_m \Delta t \leq \frac{\Delta h}{\sqrt{3}}. \quad (7)$$

For the 2-D case, the stability condition is

$$V_m \Delta t \leq \frac{\Delta h}{\sqrt{2}}. \quad (8)$$

Note that V_m is the maximum velocity in multilayer media.

2.3 Mur Absorbing Boundary Conditions.

In this section, the finite-difference approximations of the absorbing boundary conditions are presented. These approximations have a local truncation error of the second order in all increments. The discretized form of the boundary condition for E_z at the boundary of interest, i.e., the tangential boundary for the TM case, will now be given according to Mur. The finite-difference approximation was derived using centered differences in both the space and the time increments—it has a local truncation error of the second order in all increments. The first approximation for E_z is discretized as follows:

$$E_z^{n+1}(0,j) = E_z^n(1,j) + \frac{c_0\delta t - \delta}{c_0\delta t + \delta} (E_z^{n+1}(1,j) - E_z^n(0,j)). \quad (9)$$

Then, a second approximation for the 2-D TM problem is discretized as

$$E_z^{n+1}(0,j) = E_z^n(1,j) + \frac{c_0\delta t - \delta}{c_0\delta t + \delta} (E_z^{n+1}(1,j) - E_z^n(0,j)) - \frac{\mu_0 c_0}{2(c_0\delta t + \delta)} \times$$

$$H_x^{n+1/2}(0,j + 1/2) = H_x^{n+1/2}(0,j - 1/2) + H_x^{n+1/2}(1,j + 1/2) - H_x^{n+1/2}(1,j - 1/2)), \quad (10)$$

where $c_0 = \frac{1}{\sqrt{\epsilon_0 \mu_0}}$ and where the z-dependence of the fields have been deleted from our notation

since the value of z is the same in all terms. Centered differences were used for deriving (10), and these finite-difference approximations also have a local truncation error of the second order in all increments.

2.4 Sine Wave Pulse. The excitation pulse used is sinusoidal in shape. It will propagate in the +z direction and will have the representation of

$$J_z = \sin(2\pi ft), \quad (11)$$

where

$$f = 1/(50 \cdot dt). \quad (12)$$

3. SUMMARY/RESULTS

Two-dimensional TM electromagnetic scattering of a sine source disturbance is numerically solved using the FD-TD method with Mur absorbing boundary conditions. Figure 1 depicts the z component of the electric field intensity distribution with respect to the x and y planes at a very early time step of the disturbance development. Figures 2–5 depict the same distributions but at progressive times to illustrate the source disturbances growth from center excitation to the outer boundaries of the 2-D mesh. The distributions depicted in this analysis show the time development of the two-dimensional wave emanating from the sinusoidal point source projected in the z-direction which was introduced as a soft source in equation (5) itself as proposed by Taflov (1980).

An analogous program can be written for the transverse-electric (TE) case that will be another followup study to this particular work. In addition, the program can also be extended to the case of three-dimensional (3-D) electromagnetic propagation from a variety of sources at different locations of the mesh.




Figure 1. Distribution of electric field intensity (V/m) at time step = 50.




Figure 2. Distribution of electric field intensity (V/m) at time step = 75.




Figure 3. Distribution of electric field intensity (V/m) at time step = 100.




Figure 4. Distribution of electric field intensity (V/m) at time step = 150.




Figure 5. Distribution of electric field intensity (V/m) at time step = 200.

INTENTIONALLY LEFT BLANK.

4. REFERENCES

- Engquist, B., and A. Majda. "Absorbing Boundary Conditions for the Numerical Simulation of Waves." Math. Comp., vol. 31, pp. 629–651, July 1977.
- Kunz, K. S., and K. -M. Lee. "A Three-Dimensional Finite-Difference Solution of the External Response of an Aircraft to a Complex Transient EM Environment: Part I—The Method and Its Implementation." IEEE Trans. Electromagn. Compat., vol. EMC-20, pp. 328–333, May 1978.
- Merewether, D. E. "Transient Currents Induced on a Metallic Body of Revolution by an Electromagnetic Pulse." IEEE Trans. Electromagn. Compat., vol. EMC-13, pp. 41–44, May 1971.
- Mur, G. "Absorbing Boundary Conditions for Finite-Difference Approximation of the Time Domain Electromagnetic Field Equations." IEEE Trans. Elec. Comp., vol. EMC-23, pp. 1073–1077, 1981.
- Taflove, A. "Application of the Finite-Difference Time-Domain Method to Sinusoidal Steady-State Electromagnetic Penetration Problems." IEEE Trans. Electromagn. Compat., vol. EMC-22, pp. 191–202, 1980.
- Taflove, A., and M. E. Brodwin. "Numerical Solution of Steady-State Electromagnetic Scattering Problems Using the Time-Dependent Maxwell's Equations." IEEE Trans. Microwave Theory Tech., vol. MTT-23, pp. 623–630, August 1975.
- Taylor, C. D., D. -H. Lam, and T. H. Shumpert. "Electromagnetic Pulse Scattering in Time-Varying Inhomogeneous Media." IEEE Trans. Antennas Propagat., vol. AP-17, pp. 585–589, September 1969.
- Yee, K. S. "Numerical Solution of Initial Boundary Value Problems Involving Maxwell's Equations in Isotropic Media." IEEE Trans. Antennas Prop., vol. AP-14, pp. 302–307, May 1966.

INTENTIONALLY LEFT BLANK.

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
2	DEFENSE TECHNICAL INFO CTR ATTN DTIC DDA 8725 JOHN J KINGMAN RD STE 0944 FT BELVOIR VA 22060-6218
1	HQDA DAMO FDQ ATTN DENNIS SCHMIDT 400 ARMY PENTAGON WASHINGTON DC 20310-0460
1	US MILITARY ACADEMY MATH SCI CTR OF EXCELLENCE DEPT OF MATHEMATICAL SCI ATTN MDN A MAJ DON ENGEN THAYER HALL WEST POINT NY 10996-1786
1	DIRECTOR US ARMY RESEARCH LAB ATTN AMSRL CS AL TP 2800 POWDER MILL RD ADELPHI MD 20783-1145
1	DIRECTOR US ARMY RESEARCH LAB ATTN AMSRL CS AL TA 2800 POWDER MILL RD ADELPHI MD 20783-1145
3	DIRECTOR US ARMY RESEARCH LAB ATTN AMSRL CI LL 2800 POWDER MILL RD ADELPHI MD 20783-1145
<u>ABERDEEN PROVING GROUND</u>	
2	DIR USARL ATTN AMSRL CI LP (305)

NO. OF
COPIES ORGANIZATION

1 DIR USARL
 ATTN AMSRL IS
 J GANTT
 2800 POWDER MILL RD
 ADLEPHI MD 20783-1197

1 DIR USARL
 ATTN AMSRL IS C
 COL M KINDL
 GIT 115 O'KEEFE BLDG
 ATLANTA GA 30332-0800

ABERDEEN PROVING GROUND

7 DIR, USARL
 ATTN: AMSRL-IS-C,
 R HELFMAN
 J DUMER
 AMSRL-IS-CI,
 B BROOM
 T KORJACK (4 CP)

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188	
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project(0704-0188), Washington, DC 20503.				
1. AGENCY USE ONLY (Leave blank)	2. REPORT DATE June 1997	3. REPORT TYPE AND DATES COVERED Final, May 96 - Dec 96		
4. TITLE AND SUBTITLE A Two-Dimensional Transverse Magnetic Propagation Model of a Sine Wave Using Mur Boundary Conditions		5. FUNDING NUMBERS 4B010503350000		
6. AUTHOR(S) T. A. Korjack				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army Research Laboratory ATTN: AMSRL-IS-CI Aberdeen Proving Ground, MD 21005-5067		8. PERFORMING ORGANIZATION REPORT NUMBER ARL-TR-1379		
9. SPONSORING/MONITORING AGENCY NAMES(S) AND ADDRESS(ES)		10. SPONSORING/MONITORING AGENCY REPORT NUMBER		
11. SUPPLEMENTARY NOTES				
12a. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution is unlimited.		12b. DISTRIBUTION CODE		
13. ABSTRACT (Maximum 200 words) A two-dimensional (2-D) transverse magnetic formulation of a propagating sine wave source disturbance was numerically simulated using the finite difference-time domain (FD-TD) methodology. The nonreflecting boundary conditions due to Mur were used at the boundary surfaces. Electric field intensity distributions resulted over a progressive time expansion to illustrate the propagation effect over the entire 2-D mesh. The imposition of the Mur boundary algorithm produced accurate results when the second approximation was used and when the source was located reasonably far from the mesh boundary.				
14. SUBJECT TERMS transverse magnetic, Mur boundary conditions		15. NUMBER OF PAGES 20		
		16. PRICE CODE		
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT UL	

INTENTIONALLY LEFT BLANK.

USER EVALUATION SHEET/CHANGE OF ADDRESS

This Laboratory undertakes a continuing effort to improve the quality of the reports it publishes. Your comments/answers to the items/questions below will aid us in our efforts.

1. ARL Report Number/Author ARL-TR-1379 (Korjack) Date of Report June 1997
2. Date Report Received _____
3. Does this report satisfy a need? (Comment on purpose, related project, or other area of interest for which the report will be used.) _____

4. Specifically, how is the report being used? (Information source, design data, procedure, source of ideas, etc.) _____

5. Has the information in this report led to any quantitative savings as far as man-hours or dollars saved, operating costs avoided, or efficiencies achieved, etc? If so, please elaborate. _____

6. General Comments. What do you think should be changed to improve future reports? (Indicate changes to organization, technical content, format, etc.) _____

CURRENT
ADDRESS

Organization

Name

E-mail Name

Street or P.O. Box No.

City, State, Zip Code

7. If indicating a Change of Address or Address Correction, please provide the Current or Correct address above and the Old or Incorrect address below.

OLD
ADDRESS

Organization

Name

Street or P.O. Box No.

City, State, Zip Code

(Remove this sheet, fold as indicated, tape closed, and mail.)
(DO NOT STAPLE)

DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS

BUSINESS REPLY MAIL

FIRST CLASS PERMIT NO 0001,APG,MD

POSTAGE WILL BE PAID BY ADDRESSEE

DIRECTOR
US ARMY RESEARCH LABORATORY
ATTN AMSRL IS CI
ABERDEEN PROVING GROUND MD 21005-5067

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

